



WR-62 Waveguide E-Bend with UG-419/U Flange
Operating from 12.4 GHz to 18 GHz

TECHNICAL DATA SHEET

PE-W62B001

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	12.4		18	GHz
VSWR			1.08:1	

Mechanical Specifications

Waveguide Size	WR-62		
Waveguide Design	Standard		
Description	Flange 1	Waveguide	Flange 2
Interface	UG-419/U	WR-62	UG-419/U
Material	Copper Alloy	Copper Alloy	Copper Alloy
Plating	Paint	Paint	Paint

Compliance Certifications (visit www.Pasternack.com for current document)

- RoHS Compliant
- REACH Compliant 06/16/2014
- Notes:
 - Values at +25 °C, sea level

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: WR-62 Waveguide E-Bend with UG-419/U Flange Operating from 12.4 GHz to 18 GHz PE-W62B001




WR-62 Waveguide E-Bend with UG-419/U Flange
Operating from 12.4 GHz to 18 GHz

TECHNICAL DATA SHEET

PE-W62B001

Outline Drawing



WR-62 Waveguide E-Bend with UG-419/U Flange Operating from 12.4 GHz to 18 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [WR-62 Waveguide E-Bend with UG-419/U Flange Operating from 12.4 GHz to 18 GHz PE-W62B001](http://www.pasternack.com/wr-62-waveguide-e-bend-12.4-18-ghz-pe-w62b001-p.aspx)

URL: <http://www.pasternack.com/wr-62-waveguide-e-bend-12.4-18-ghz-pe-w62b001-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.